



## RATCHET OPENER



### FIELD OF THE INVENTION

The present invention relates to openers, and particular to a ratchet opener,  
5 wherein by controlling the adjusting sheet, the objects of unidirectional, bi-directional, and idle rotations are achieved. The operation is easy and convenient.

### BACKGROUND OF THE INVENTION

10 In the prior art, a stand type ratchet opener has a seat installed on a handle. An approximate C shape stopper protruded from the seat. A receiving space in a center of the stopper receives a tool rod of a ratchet unit. A left and a right stop of the ratchet unit are received in the left and right slots between the stopper and the cylinder. The cylinder has a left projection and a right  
15 projection corresponding to the left and right stops for engaging a left and a right concave portion at a rear middle section of the left and right stop. Thereby, the left and right stop swings along the engaging portions, but not to engage a toothed section of the tool rod. Thereby, the seat can drive the tool rod to rotate.

20 In another prior art, a seat is installed to a handle. A receiving portion at a center of the seat serves to receive a tool rod of a ratchet unit. Two sides of the receiving portion are extended with a left receiving chamber and a right receiving chamber symmetrically for installing the left and right stops of the ratchet unit. The seat has two protrusions for supporting the left and right  
25 stops. Thereby, the left and right stop swings along the engaging portions, but not to engage a toothed section of the tool rod. Thereby, the seat can drive the

tool rod to rotate.

In above mentioned two prior arts, the left and right stops are used to transversally control the rotation direction of the tool rod. Thereby, the transversal control has the following problems. The components of the ratchet  
5 opener are too complicated to be manufactured easily. As a result, the assembly work is difficult and some techniques in assembly must be learnt so as to increase the burdens of workers. Moreover, since the assembly work is complicated so that more workers are necessary. However, this increases the cost.

10

## **SUMMARY OF THE INVENTION**

Accordingly, the primary object of the present invention is to provide a ratchet opener which comprises a rod body; a lower end of the rod body being protruded with a non-round cylinder; a handle having a receiving chamber; a  
15 ratchet device having a seat; a center of the seat being installed with a first via hole; a top surface of the seat having two axially grooves; each groove being installed with an elastomer and a ratchet block; an adjusting sheet placing above the seat; and a ratchet sheet being installed above the adjusting sheet. Each ratchet block has a teethed inclined surface; the teeth surfaces of the two ratchet  
20 blocks are symmetrical to a center of the seal. The adjusting sheet has two through holes which are arranged corresponding to the two ratchet blocks of in the seat. A center of the adjusting sheet is installed with a second via hole; and the ratchet block is installed with a non-round bucking hole corresponding to the cylinder at the lower end of the rod body. When the ratchet device is  
25 assembled, the rod body will pass through the buckling hole; first via hole and the second via hole and the seat is buckled to the receiving chamber of the

handle.

The various objects and advantages of the present invention will be more readily understood from the following detailed description when read in conjunction with the appended drawing.

5

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a structural schematic view of the ratchet opener of the present invention.

Fig. 2 is a schematic view of the ratchet sheet of the ratchet opener of the  
10 present invention.

Fig. 3 is a perspective view of the ratchet opener of the present invention.

Fig. 4 is an upper cross section view showing the first operation of the ratchet opener of the present invention.

Fig. 5 is an upper cross section view showing the second operation of the  
15 ratchet opener of the present invention.

Fig. 6 is an upper cross section view showing the third operation of the ratchet opener of the present invention.

Fig. 7 is a partial cross section view showing the first operation of the ratchet opener of the present invention.

Fig. 8 is a partial cross section view showing the second operation of the  
20 ratchet opener of the present invention.

Fig. 9 is a partial cross section view showing the third operation of the ratchet opener of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

In order that those skilled in the art can further understand the present invention, a description will be described in the following in details. However, these descriptions and the appended drawings are only used to cause those skilled in the art to understand the objects, features, and characteristics of the present invention, but not to be used to confine the scope and spirit of the present invention defined in the appended claims.

Referring to Figs. 1 to 3, the ratchet opener of the present invention is illustrated. The ratchet opener of the present invention includes a round rod body 10. A lower end of the rod body 10 is formed as a hexagonal cylinder. A top of the rod body 10 is formed with a hole 11.

A handle 20 is formed with a receiving chamber 21. Each of two ends of the receiving chamber 21 is formed with respective bucking slot 22, respectively.

A ratchet device includes a seat 31. A center of the seat 31 is formed with a first via hole 311. A lower end of the ratchet device 31 has a protrusion portion 313 for buckling to the bucking slots 22. A top of the ratchet device has two axial grooves 312. Each groove 312 is installed with an elastomer 32 and a ratchet block 33. An adjusting sheet 34 is placed upon the ratchet blocks 33. A ratchet sheet 35 is placed upon the adjusting sheet 34.

The ratchet teeth 331 of each ratchet block 33 are formed on an inclined surface. The two ratchet blocks 331 are oppositely arranged so as to drive the ratchet sheet 35 to rotate along two different directions. Each adjusting sheet 34 is formed with two through holes 341 which are arranged corresponding to the ratchet blocks 33. A center of the adjusting sheet 34 is formed with a

second via hole 342. A periphery of the adjusting sheet 34 is formed with a projection 343. Moreover, the ratchet sheet 35 is installed with a hexagonal bucking hole 351 corresponding to the lower end of the rod body 10.

5 A sleeve 40 has a round hole 41 at a center thereof. A periphery of the sleeve 40 is formed with a radial cambered recess 42. After assembly, the projection 343 of the adjusting sheet 34 will protrude out of the cambered recess 42 so as to control the rotation direction of the ratchet opener.

10 In assembly of above mentioned structure, the groove 312 of the seat 31 will receive the elastomer 32 and the ratchet block 33. Then the adjusting sheet 34 and ratchet sheet 35 are located above the ratchet block 33. Then rod body 10 passes through the buckling hole 351, the second via hole 342 and the first via hole 311. Then the C ring 50 serves to fix the rod body 10. After fixing, a lower end of the seat 31 is buckled in the receiving chamber 21 of the handle 20. Finally, the sleeve 40 encloses an upper end of the seat 31 and the projection 15 343 of the adjusting sheet 34 protrudes out from the cambered recess 42 of the sleeve 40.

By the above ratchet device, when only one ratchet block 33 protrudes from the through hole 341 to be engaged with the ratchet sheet 35 (referring to Fig. 4 and 7), since the ratchet block 33 is an unidirectional teethed block, the ratchet 20 opener can only drive the ratchet sheet 35 so as to drive the rod body 10 to rotate unidirectionally. If the ratchet opener rotates along a reverse direction, the ratchet sheet 35 cannot be driven so as to rotate idly. When the adjusting sheet 34 is adjusted, the ratchet block 33 protrudes out of the through hole 341 to buckle the ratchet sheet 35 (referring to Figs. 5 and 8). Thus, a complete 25 different action is presented. It only causes that the ratchet opener drive the ratchet block 33 to rotate unidirectionally. Similarly, when the two ratchet

blocks 33 are buckled to the ratchet sheet 35 simultaneously (referring to Figs. 6 to 9), the ratchet opener will drive the ratchet sheet 35 to achieve the object of bi-directional rotation.

5 In use, by controlling the adjusting sheet 34, the objects of unidirectional, bi-directional, and idle rotations are achieved. The operation is easy. The assembly work is easy and convenient and the structure is simple. Thereby, the difficulty in manufacturing is reduced.

10 The present invention is thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the present invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.